Reolink

E321

3MP Super HD, Pan & Tilt & 2-Way Talk; Versatile Smart Home WiFi IP Camera

- 3MP Super HD
- Pan & Tilt
- Two-Way Audio

Specifications

Video & Audio	
Image Sensor	1/3" CMOS sensor
Resolution	2304x1296 (3 megapixels)@15FPS
Lens	f=4mm, F=2.0, with IR cut
Video Compression	H.264
Field of View	Horizontal: 77° Vertical: 41°
Pan/Tilt Angle	Horizontal: 355° Vertical: 50°
Day & Night	IR-cut filter with auto-switching
Infrared Night Vision	Up to 12 meters (40ft)
Frame Rate	Up to 20fps
Audio	Two-way audio
Interface	
Power Port	Type-C USB
System	Reset button

Storage	microSD card slot (Max. 512GB)
Audio	Built-in microphone and speaker
Wi-Fi & Bluetooth	
Wireless Standard	IEEE 802.11ax/b/g/n
Operating Frequency	2.4GHz
Wireless Security	WPA/WPA2/WPA3
Bluetooth	Supported
Software	
Frame Rate	Mainstream: 2fps - 20fps (default: 20fps) Substream: 4fps - 20fps (default: 10fps)
Code Rate	Mainstream: 2048Kbps - 4096Kbps (default: 2560Kbps) Substream: 64Kbps - 512Kbps (default: 256bps)
Browsers Supported	Unsupported
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Detection	Motion detection/Human Detection/Pet Detection/ Crying Detection
Recording Modes	Motion recording (default); scheduled recording; 24/7 recording
Protocols & Standards	SSL, TCP/IP, UDP, IPv4, UPnP, SMTP, NTP, DHCP, DNS, DDNS, P2P
Maximal User Access	Max. 20 users (1 admin & 19 user); Max. 12 simultaneous streams (2 main & 10 sub streams)
Work with	Alexa, Google Assistant
Privacy Mode	Supported
Time Lapse	Supported
Auto-Tracking	Supported
Working Environment	
Operating Temperature	-10°C~+55°C (14°F~131°F)
Operating Humidity	20% ~ 85%
Size & Weight	

Dimensions	Φ73×114 mm
Weight	167 g
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.

Gallery & Specs

1. CDS
2. Black Lens Ring
3. LED
4. Microphone
5. Reset
6. Micro SD Card Slot
7. Speaker
8. Type-C USB port