Reolink

## Argus Eco Ultra

**Smart 4K 8MP standalone battery/solar-powered camera with 5/2.4 GHz dual-band Wi-Fi, and color night vision, no base station or subscription fees required.**

- 4K 8MP Ultra HD
- Battery/Solar-Powered
- 5/2.4 GHz Dual-Band WiFi
- Easy & Flexible Installation



## Specifications

| **Video & Audio** | |
|---|---|
| Image Sensor | 1/2.7"CMOS sensor |
| Resolution | 3840 x 2160 (8 megapixels) @15fps |
| Video Compression | H.265 |
| Field of View | Horizontal: 105° Vertical: 55° Diagonal: 125° |
| Infrared Night Vision | Up to 10 meters (33ft); LED: 8pcs/1.1w/850nm (Auto-switching with IR-cut filter) |
| Color Night Vision | Spotlights: 2pcs/2w/6500k |
| Frame Rate | Mainstream: 10fps - 15fps (default: 15fps) Substream: 10fps - 15fps (default: 15fps) |
| Code Rate | Mainstream: 1024Kbps - 4096Kbps (default: 3072Kbps) Substream: 64Kbps - 672Kbps (default: 672Kbps) |
| Audio | Two-way audio |
| **Power** | |

| | |
|---|---|
| Battery | 21.6Wh rechargeable battery (Battery life varies based on settings, usage & temperature) |
| Solar | Reolink Solar Panel |
| **Interface** | |
| Power Port | USB Type-C port |
| SD Card Slot | Supports Max. 512GB microSD card |
| Reset Button | YES |
| Audio In/Out | Built-in microphone and speaker |
| **Wi-Fi** | |
| Wireless Standard | IEEE 802.11 a/b/g/n |
| Operating Frequency | 2.4GHz/5GHz |
| Wireless Security | WPA/WPA2 |
| **Software** | |
| OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| Protocols & Standards | SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P |
| User Access | Max. 12 simultaneous streams (2 main & 10 sub streams) |
| **Other Features** | |
| Smart Alarm | PIR detection; person detection; vehicle detection; pet detection |
| PIR Detection Distance | Adjustable up to 10m (33ft) |
| PIR Detection Angle | 110° horizontal |
| Recording Modes | Triggered recording |
| Time Lapse | YES |
| Smart Home Compatibility | Google Assistant |
| Cloud Storage | Supports Reolink Cloud (available in selected countries) |
| **Working Environment** | |
| | -10°C~+55°C (14°F~131°F) |

| | |
|---|---|
| Operating Temperature | |
| Operating Humidity | 20% ~ 85% |
| Weatherproof | IP66 |
| **Mechanical** | |
| Dimensions | 191 x 75 x 75mm |
| Weight Battery Included | 431g |
| **Warranty** | |
| Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/. |

## Gallery & Specs




