

# Reolink Professional Series

## RP-PN8

12-Channel PoE NVR for 24/7 Continuous Recording



|  |  |   |  |
|--|--|---|--|
|  PoE Easy Setup | <b>16MP</b><br>Up to 16MP Resolution   | <b>2TB</b><br>Pre-installed 2TB HDD   | <b>32TB</b><br>Support Maximum 32TB  |
|  Heat Map       |  240Mbps Input / Output Bandwidth |  File Encryption |  Centralized Management |
|  Remote Access  |  Local Access                     |  24/7 Recording  |  |

# Reolink Feature Descriptions

## 16MP Ultra HD Footage

Supports up to 16MP resolution from connected cameras, capturing ultra-clear footage in vivid color or sharp black and white—day or night. Every detail stays in sharp focus, ensuring enhanced clarity for critical surveillance needs.

## All-in-One Control & Storage System

A centralized solution for video storage and alarm management across all Reolink cameras—wired, wireless, PoE, and doorbells (excluding 4G models). Equipped with 8 PoE ports and expandable to 12 channels, the system supports up to 8 PoE/Wi-Fi cameras plus 4 battery-powered Wi-Fi cameras, or up to 12 battery-powered Wi-Fi cameras in total. This flexible setup allows you to build a customized surveillance system tailored to your security needs.

## Massive Enterprise-Grade Storage Capacity

With a pre-installed 2TB HDD and expandable storage up to 32TB (1x16TB SATA, 1x16TB e-SATA), the NVR is ideal for large-scale surveillance deployments, ensuring reliable data archiving and quick access to historical video records.

## 24/7 Continuous Recording

Experience the peace of mind that comes with 24/7 local recording. The NVR captures and stores footage continuously, ensuring no moment is missed and enabling instant playback whenever you need it.

## AI Video Search

Quickly locate targets in local recordings by entering descriptive phrases like “white van” or “person wearing a hat” using a virtual or physical keyboard. For faster searches without typing, use the structured click-to-select panel—choose attributes like Top: T-shirt and Color: Red to auto-generate search terms, then simply click Search. AI Video Search significantly shortens investigation time, enhancing response speed and decision-making efficiency. All searches are performed locally, ensuring data privacy with no additional costs.

## Heat Map

The heat map function visually displays foot traffic patterns by analyzing movement and dwell time within a specific area. Commonly used in high-traffic environments like shopping malls, supermarkets, and museums, it generates a color-coded map that highlights where people gather and how long they stay—offering clear, intuitive insights for space utilization and security optimization.

## Multiple Access Methods

Access the NVR locally via a connected monitor or remotely through the Reolink app and client software. Enjoy live viewing and playback anytime, anywhere—whether you're on-site or on the go.

# Reolink Specification

| <b>Video/Audio Input</b>      |   |
|-------------------------------|---|
| IP Video Input                | Supports maximum 8 wired cameras (includes PoE cameras and plug-in powered Wi-Fi cameras), and 4 battery-powered Wi-Fi cameras.         |
|                               | Supports up to 16 MP resolution for each channel  |
| Audio Input                   | Cameras with built-in MIC   |
| Incoming Bandwidth            | 240Mbps   |
| Outgoing Bandwidth            | 240Mbps   |
| <b>Video/Audio Output</b>     |   |
| Video Output                  | 1 HDMI, 1 VGA   |
| Display Resolution            | HDMI: 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768<br>VGA: 1920x1080, 1280x1024, 1280x720, 1024x768                              |
| Audio Output                  | 1 audio out channel, RCA  |
| <b>Decoding</b>               |   |
| Video Compression             | H.265 / H.264   |
| Live View/Playback Resolution | 7680*2160, 4608*1728, 4512*2512, 4096*3072, 3840*2160, 2560*2560, 2560*1920, 2560*1440, 2048*1536, 2304*1296, 1080P, 720P               |
| Synchronous Playback          | 1-4 channels (Supports only 1-channel playback if you view it in 8MP or higher resolution)  |
| <b>HDD</b>                    |   |
| SATA                          | 1 SATA interface (with or without 2TB HDD)  |
| External HDD                  | 1 eSATA interface for HDD   |
| Capacity                      | Up to 32TB (up to 16TB capacity for each HDD)   |
| <b>External Interfaces</b>    |   |
| USB Interface                 | 2 x USB 2.0   |
| Network Interface             | 8 x RJ-45, 10/100 Mbps self-adaptive PoE Ethernet interface (for IP cameras)<br>1 x RJ-45, 10/100/1000 Mbps self-adaptive (for LAN/WAN) |
| Alarm Input/Output            | N/A   |
| <b>PoE</b>                    |   |
| Max. Power per Port           | 25W   |
| Supported Standard            | IEEE 802.3 af/at  |
| <b>Network</b>                |   |
| Network Protocols             | HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, RTMP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP  |
| Browsers Supported            | Edge, Firefox, Chrome, Safari   |
| OS Supported                  | PC: Windows, Mac OS; Smart phone: iOS, Android  |
| User Access                   | 20 Users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)             |
| <b>AI</b>                     |   |
| AI Video Search               | Yes (Requires support from compatible cameras.)   |
| Person & Object Detection     | Person, Vehicle, Non-motorized vehicle, Animal and Package (Requires support from compatible cameras.)                                  |
| Perimeter Protection          | Line Crossing Alert, Zone Intrusion Alert, Zone Loitering Alert (Requires support from compatible cameras.)                             |
| Smart Event Detection         | Object Removal Detection(Beta), Forgotten Object Detection(Beta) (Requires support from compatible cameras.)                            |
| Heat Map                      | Yes   |
| <b>General</b>                |   |
| Power Supply                  | DC 52V/2.3A   |
| Power Consumption             | <10W (without HDD & PoE)  |
| Working Environment           | Temperature: -10°C ~ + 45°C (14°F ~ 113°F); Humidity: 10% ~ 90%   |
| Dimensions                    | 255mmx50mmx211mm  |
| Weight                        | 1.4kg (Without HDD)<br>1.8kg (With HDD)   |
| <b>Warranty</b>               |   |
| Limited Warranty              | 3-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> . |

# Reolink Product Explanation

① Power LED

② HDD LED

③ USB PORT

④ Power Switch

⑤ Power Input

⑥ Audio Out

⑦ eSATA Port



⑧ VGA Port

⑨ HDMI Port


⑩ LAN Port

⑪ USB Port


⑫ PoE Ports




## What's in the Box (NVR System)




NVR




NVR Power Adapter



HDMI Cable



USB Mouse



1M Network Cable



Quick Start Guide